



new

Caratteristiche

Modelli	Video	Risoluzione	Porte seriali	Ethernet
GHFE4043C	4,3"	480 x 272	2	no
GHFE4043E				si
GHFE007	7"	1024 x 600	4	si
GHFE6070C		800 x 480	2	no
GHFE6070WE		800 x 480	2	si
GHFE010	10"	1024 x 768	4	si
GHFE6100C		1024 x 600	2	no
GHFE6100E		1024 x 600	2	si
GHFE4121X	12,1"	1024 x 768	3	si
GHFE6156H	15,6"	1920 x 1080	3	si
GHFE5170	17"	1280 x 1024	3	si
GHFE5220	22"	1920 x 1080	3	si
GHFE5320	32"	1920 x 1080	3	si

Specifiche

Modelli	Alimentazione	Consumo	Temperatura	Umidità
GHFE4043C	24VDC, 18-28VDC	5W	0 - 50°C	10 - 90%
GHFE4043E		5W	-20 - +70°C	
GHFE007		6W	-10° - +60°C	
GHFE6070C		10W	0 - 50°C	
GHFE6070WE		10W	0 - 50°C	
GHFE010		8W	-10° - +60°C	
GHFE6100C		10W	0 - 50°C	
GHFE6100E		10W	0 - 50°C	
GHFE4121X		15W	-20 - +70°C	
GHFE6156H		18W	0 - 50°C	
GHFE5170		18W	-10° - +60°C	
GHFE5220		20W	0 - 50°C	
GHFE5320		20W	-20 - +60°C	

Software di configurazione : Fstudio

Grado di protezione : IP65 frontale

Certificazione : CE EN61000-6-2:2005